

## TERM-seal™ MULTI-PURPOSE ACTIVE

### Termite & Waterproof Barrier

TERM-seal™ Multi-Purpose Active is a highly engineered, acrylic polymer-based liquid which upon curing forms a seamless, flexible, termite resistant and waterproof membrane. Applied by brush, roller or heavy-duty airless spray gun, applications include wall backfills, internal walls, internal wet areas, construction joints, step downs & cavities.

- Used in conjunction with TERM-seal™ Reo-Band FG to form a perimeter and damp-course barrier to cyclone rated knock-out infill construction
- Dual water-proof/termite single application Tested by CSIRO as an approved waterproofing compound and complies to Building Code of Australia Volume 2, AS3660.1-2014., AS/NZS 4347.6 and AS/NZS 4858-2004. And applied as waterproofing to back-filled walls to meet the requirements of A.S. 3740
- Used as a simple, easy to apply slab edge exposure perimeter treatment, or to waterproof slab edges.
- Applied to cavities to form a termite proof perimeter barrier.
- Used to treat construction joints across concrete slabs



APVMA Approval No: 62740/43873

**Available in:-  
15 litre buckets only  
(White Bucket)**

## TERM-seal™ PRIME COAT

### Surface Primer

TERM-seal™ Prime Coat is a high-quality acrylic based primer for use on concrete and masonry surfaces and specifically designed for use with TERM-seal™ Multi-Purpose Active and TERM-seal™ Sealant Active for both internal and external applications.

TERM-seal™ Prime Coat must be applied prior to the first coat of TERM-seal™ Multi-Purpose Active or TERM-seal™ Sealant Active in all applications as it provides the necessary texture to ensure correct adhesion to the surface treated.

**Available in:-  
4 litre buckets (white),  
10 litre buckets (pink)**



## TERM-seal™ REO-BAND FG

### Glass Fibre Mat

TERM-seal™ Reo-Band FG is non-woven fibreglass mat, specially manufactured with a wax type coating which provides ease of use. Used with TERM-seal™ Sealant Active and TERM-seal™ Multi-Purpose Active Coating to reinforce joints and corners.

- Used with the TERM-seal™ Sealant Active
- Used with the TERM-seal™ Multi-Purpose Active Coating

**Available in:- Rolls of 100mm,  
130mm, 205mm and 502mm  
width, with a length of approx 160mtrs**



### Contact your local - TERMSEAL AUSTRALIA REPRESENTATIVE

Nigel Stafford (NSW/ACT) 0484 091 993  
Peter Brigden (QLD) 0409 766 944

John Turner (VIC/SA) 0438 711 886  
Martin Kearney (WA) 0429 668 919

